

	TECHNICAL PRODUCT DOCUMENTATION	MEZ-12 - DTR
		Page: 1 Pages: 8

SINGLE-WAY MANIFOLDS
(VALVES) type:
MEZ-12-00
MEZ-12-01
MEZ-12-03

	TECHNICAL PRODUCT DOCUMENTATION	MEZ-12 - DTR
		Page: 2 Pages: 8

LIST OF CONTENTS:

1. INSTRUCTIONS AND WARNINGS	3
2. APPLICATION	3
3. DESIGN	4
4. TECHNICAL DATA	4
5. ORDERING AND CONDITIONS OF DELIVERY	4
6. ORDERING METHOD	5
7. MANUFACTURER'S DECLARATION	6
8. ENCLOSURES	7



	TECHNICAL PRODUCT DOCUMENTATION	MEZ-12 - DTR
		Page: 3 Pages: 8

1. INSTRUCTIONS AND WARNINGS

In case of not fulfilling the recommendations and warnings one can have serious body injuries, and/or serious material damages. The attendance personnel must be properly trained and acquainted with all the safety recommendations and warnings.

Reliable and safe operation of the valve is dependent of providing the proper transportation, storing, assembling and start-up.


The present Technical Product Documentation contains important remarks in the scope of safety which were denoted with the below shown pictograms:

	<p>This sign means: Indicator</p> <p>This “Indicator” shows an operation or process being of essential importance for proper operation of the device. Material damages can occur in case of not observing this recommendation.</p>
	<p>This sign means: Warning</p> <p>This “Warning” shows an operation or process which in case of improper operation can cause danger to the attendance personnel or serious material damages.</p>

2. APPLICATION

The single-way manifold (valve) type DN 5, PN 320 is applied in the industrial automation Instrumentation & Controls systems.

Block diagram



	TECHNICAL PRODUCT DOCUMENTATION	MEZ-12 - DTR
		Page: 4 Pages: 8

3. DESIGN

The manifold (valve) is made of steel, grade 15HM or acid-proof steel, grade 1H18N9T (321ss).

The impulse ends of the valve are adapted for welding the tubes of 12 and 14 dia. or they are equipped with self-clamping (self-locking) rings of 12 and 14 dia.

Manifold's (valve's) equipment – the manifolds (valves) are provided with setting key to enable quick manifold (valve) servicing.

4. TECHNICAL DATA

Permissible operating temperatures:

- for manifold (valve) MEZ - 12 - 00 up to 400° C
- for manifold (valve) MEZ - 12 - 01 up to 250° C
- for manifold (valve) MEZ - 12 - 03 up to 200° C

Manifold's (Valve's) type	Version	Material
MEZ-12-00	Normal	15 HM
MEZ-12-01	Acidproof	1H18N9T (321ss)
MEZ-12-03	For oxygen	1H18N9T (321ss)

Passage diameter

5 mm

Mass

1,5 kg

5. ORDERING AND CONDITIONS OF DELIVERY

The delivery consists of the following elements:

- | | |
|--|------|
| 1. Complete manifold (valve) MEZ-12- | 1 pc |
| 2. Key, complete, drawing no. ME2-0153 | 1 pc |
| 3. Technical Product Documentation | 1 pc |
| 4. Guarantee Card, with Acceptance Certificate | 1 pc |

The manifold (valve) is delivered in the cardboard packing.

Information for the Customers: upon a separate order we can deliver these spare parts:

- | | |
|--|--------|
| 1. Stem seal ring – 15 dia. / 9 dia. x 6 | 2 pcs. |
|--|--------|



**Nominal pressure P_{nom} for impulse 12 dia. tubes,
sealed with self-locking rings, is 16 MPa.**

6. ORDERING METHOD

MEZ-12-	Single-way straight valves		
CODE1	VALVE BODY MATERIAL TYPE		
00/	Steel 15HM		
01/	Steel 1H18N9T (321 ss) acid-proof		
03/	Steel 1H18N9T (321 ss) for oxygen		
CODE2	APPLICATION AND CONNECTING TO TRANSMITTER		
0-	by impulse tube		
CODE3	IMPULSE HOLES SPACING		
0-	not concern (one hole)		
CODE4	IMPULSE ENDS		
1	φ 14 for welding with ball-end		
2	φ 12 for welding with ball-end		
3	φ 14 with self-locking ring		
4	φ 12 with self-locking ring		
5	ø14 for welding with flat end		
6	ø12 for welding with flat end		
MEZ - 12 - 00 / 0 - 0 - 1			
VALVE TYPE			

	TECHNICAL PRODUCT DOCUMENTATION	MEZ-12 - DTR
		Page: 6 Pages: 8

7. MANUFACTURER'S DECLARATION



CONTROLMATICA ZAP-PNEFAL Sp. z o. o.
ul. Krotoszyńska 35
63-400 Ostrów Wielkopolski
www.controlmatica.com.pl



Ostrów Wielkopolski, 10 października 2008r.

OŚWIADCZENIE PRODUCENTA

Oświadczamy, że wyroby MEZ – 10 ÷ 25 spełniają wymagania dyrektywy „Urządzenia Ciśnieniowe” 97/23/WE według art. 3 ust. 3.

Są wykonane zgodnie z uznaną praktyką inżynierską i nie podlegają oznaczeniu CE.

Stosowane jako osprzęt ciśnieniowy zbiorników do gazów zaliczanych do płynów grupy 1 (klasyfikacja wg dyrektywy) mają ograniczenie ciśnienia do 20MPa.

KIEROWNIK
DZIAŁU TECHNICZNEGO
mgr inż. Krzysztof Idzior

PREZES ZARZĄDU
Sebastian Moch

Ostrów Wielkopolski, on 10th October 2008

PRODUCER'S DECLARATION

We declare that the products type MEZ-10...25, meet the requirements of the EU Directive „Pressure-type Equipment” no. 97/23/WE, according to Article 3, section 3.

These products are made with the acknowledged engineering practice and are not subject to the CE marking.

These products are used as the pressure accessories of tanks for gases included into the Group 1 liquids (classification acc. to the a. m. Directive) and have pressure limitation up to 20 MPa.


Signed by:
Technical Dept. Manager
(-) illegible signature
mgr inż. Krzysztof Idzior

Signed by:
President of the Board
(-) illegible signature
Sebastian Moch

8. ENCLOSURES

ENCLOSURE NO. 1

Range of operating pressures in function of temperature for valves type MEZ-12-



ENCLOSURE NO. 2

Ball-type end, O. D. 12 and 14 dia. for welding,
or self-locking ring I. D. 12 and 14 dia.

